



Variable Area Flowmeter glass cone



measuring
•
monitoring
•
analysing

UVR/UTR



- Measuring range:
water: 10 - 100 l/h ... 200 - 2000 l/h
air: 0.1 - 1 ... 5 - 50 Nm³/h
- Accuracy class: 4 acc. to VDI/VDE
- p_{\max} : 10 bar;
 t_{\max} : 100 °C (65 °C for PVC)
- Connection: G 3/8, G 1/2, 3/8" NPT, 1/2" NPT
or others with adapters
- Material: stainless steel or POM-C



51

KOBOLD companies worldwide:

AUSTRALIA, AUSTRIA, BELGIUM, BULGARIA, CANADA, CHINA, CZECHIA, EGYPT, FRANCE,
GERMANY, GREAT BRITAIN, HUNGARY, INDIA, INDONESIA, ITALY, MALAYSIA, MEXICO,
NETHERLANDS, PERU, POLAND, REPUBLIC OF KOREA, ROMANIA, SPAIN, SWITZERLAND,
THAILAND, TUNISIA, TURKEY, USA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
☎ Head Office:
+49(0)6192 299-0
+49(0)6192 23398
info.de@kobold.com
www.kobold.com



Description

The flowmeters and switches model UVR and UTR for liquids and air operate on the suspended float principle: that is, the installation position is vertical and the direction of flow is from bottom to top.

The instruments have been designed as simple and thus economical measuring systems. The float for UVR and UTR is a bomb form float, whereby the indication point is the top of the float. The appliance is available with or without needle valve as well.

Applications

- Cooling water system
- Gas monitoring for burners
- Inert gas controlling

Technical Details

Installation position: vertical, flow from bottom
 Accuracy class: 4 acc. to VDI/VDE 3513
 Max. pressure: 10 bar
 Process temperature: 0 ... +100 °C
 0 ... +70 °C with contact
 0 ... +65 °C (PVC float)
 Ambient temperature: 0 ... +65 °C
 Protection: IP 65
 Connections: G 3/8, G 1/2, 3/8" NPT, 1/2" NPT
 Option: adapters (G 1/4, G 3/8, G 1/2)
 pipe connections for plastic pipes
 hose connections
 push-on connections

Materials

Fitting: stainless steel (1.4401, 1.4301) or POM-C
 Measuring tube: borosilicate glass
 Float stop: PTFE or st. steel 1.4301, 1.4401
 Float: stainless steel (1.4401, 1.4301), PVC, aluminium, PP
 Gasket: FPM, EPDM, NBR
 Valve: stainless steel (1.4401, 1.4301) (not usable as shut-off valve)

Limit Switches (option)

The flowmeters can be fitted with limit switches as an option. These limit switches are cylinder type proximity switches. The electrical connection is via 2m cable.

The following type is available: Monostable (preferably used as Min./Max. contact).

Material Combinations*

Code	Housing	Connection	Valve	Float	Gaskets	Tube
0	POM-C	POM-C	POM-C	PVC for gases PTFE for liquids	EPDM	borosilicate glass
3	1.4301	1.4301	1.4301	1.4301	FPM	
5	1.4404	1.4404	1.4404	1.4404	FPM	

* Special material combination on request



Order Details Liquids (Example: UVR-0 20H 0 I3 0)

Model	Measuring ranges Water [l/h]	Needle valve	Connection	Switch
UVR-0 UVR-3 UVR-5	20H = 10 ... 100	0 = without 1 = with valve	I3 = G $\frac{3}{8}$ N3 = $\frac{3}{8}$ " NPT YY = other	0 = none P* = 1 x PNP R* = 2 x PNP
	22H = 16 ... 160			
	24H = 25 ... 250			
	26H = 40 ... 400			
	28H* = 63 ... 630			
UTR-0 UTR-3 UTR-5	26H = 40 ... 400		I4 = G $\frac{1}{2}$ N4 = $\frac{1}{2}$ " NPT YY = other	
	28H = 63 ... 630			
	30H = 100 ... 1000			
	32H = 160 ... 1600			
	33H* = 200 ... 2000			

* Only with stainless steel float (UTR/UVR -3 and-5)


Order Details Gases (Example: UVR-0 20L 0 I3 0)

Model	Measuring ranges Air [Nm ³ /h]**	Needle valve	Connection	Switch
UVR-0 UVR-3 UVR-5	20L = 0.1 ... 1.0	0 = without 1 = with valve	I3 = G $\frac{3}{8}$ N3 = $\frac{3}{8}$ " NPT YY = other	0 = none P* = 1 x PNP R* = 2 x PNP
	22L = 0.16 ... 1.6			
	24L = 0.25 ... 2.5			
	26L = 0.4 ... 4			
	28L = 0.63 ... 6.3			
	30L = 1 ... 10			
	32L = 1.6 ... 16			
	33L* = 2 ... 20			
UTR-0 UTR-3 UTR-5	26L = 0.4 ... 4		I4 = G $\frac{1}{2}$ N4 = $\frac{1}{2}$ " NPT YY = other	
	28L = 0.63 ... 6.3			
	30L = 1 ... 10			
	32L = 1.6 ... 16			
	34L = 2.5 ... 25			
	36L = 4 ... 40			
	37L* = 5 ... 50			

* Only with stainless steel float (UTR/UVR -3 and-5)

** @ 1.013 bar abs and 20°C

Dimensions [mm]



Model	L	L ₁	L ₂	M	W	D	D ₁
UVR-xM	240	283	287.5	21	50	62	100-108
UTR-xM	340	375	375.0	17	62	62	105-114