Details of Bolting for BS and ASA pipe flanges

Flange Size	150 lb (1/16" Raised Face)				300 lb (1/16" Raised Face)				400 lb (1/4" Raised Face)				600 lb (1/4" Raised Face)				900 lb (1/4" Raised Face)				1500 lb (1/4" Raised Face)				2500 lb (1/4" Raised Face)			
Nominal	No.	Dia.	Length	Length	No.	Dia.	Length	Length	No.	Dia.	Length	Length	No.	Dia.	Length	Length	No.	Dia.	Length	Length	No.	Dia.	Length	Length	No.	Dia.	Length	Length
Pipe	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of	of
Size	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt	Bolts	Bolts	Hex Bolt	Studbolt
1/2"	4	1/2"	1.3/4"	2.1/4"	4	1/2"	2"	2.1/2"					4	1/2"	2.1/2"	3"					4	3/4"	3.1/2"	4"	4	3/4"	4.1/2"	4.3/4"
3/4"	4	1/2"	2"	2.1/4"	4	5/8"	2.1/2"	2.3/4"					4	5/8"	2.3/4"	3.1/4"					4	3/4"	3.3/4"	4.1/4"	4	3/4"	4.1/4"	4.3/4"
1"	4	1/2"	2"	2.1/2"	4	5/8"	2.1/2"	3"					4	5/8"	3"	3.1/2"	1	For the	se size:	S	4	7/8"	4.1/4"	4.3/4"	4	7/8"	4.3/4"	5.1/4"
1.1/4"	4	1/2"	2.1/4"	2.1/2"	4	5/8"	2.3/4"	3"		For the	se size	S	4	5/8"	3.1/4"	3.3/4"	1	1500 lb	Flange	es	4	7/8"	4.1/4"	4.3/4"	4	1"	5.1/4"	5.3/4"
1.1/2"	4	1/2"	2.1/4"	2.3/4"	4	3/4"	3"	3.1/2"		600 lb I	Flange	S	4	3/4"	3.1/2"	4"	1	are	used		4	1"	4.3/4"	5.1/4"	4	1.1/8	6"	6.1/2 "
2"	4	5/8"	2.3/4"	3"	8	5/8"	3"	3.1/2"		are (used		8	5/8"	3.1/2"	4"	1				8	7/8"	5"	5.1/2"	8	1"	6.1/4"	6.3/4"
2.1/2"	4	5/8"	3"	3.1/4"	8	3/4"	3.1/4"	3.3/4"					8	3/4"	4"	4.1/2"	1				8	1"	5.1/2"	6"	8	1.1/8"	7"	7.1/2"
3"	4	5/8"	3"	3.1/2"	8	3/4"	3.1/2"	4"					8	3/4"	4.1/4"	4.3/4"	8	7/8"	5"	5.1/2"	8	1.1/8"	6.1/4"	6,3/4"	8	1.1/4"	8"	8.1/2"
3.1/2"	8	5/8"	3"	3.1/2"	8	3/4"	3.3/4"	4.1/4"					8	7/8"	4.3/4"	5.1/4"												
4"	8	5/8"	3"	3.1/2"	8	3/4"	3.3/4"	4.1/4"	8	7/8"	4.3/4"	5.1/4"	8	7/8"	5"	5.1/2"	8	1.1/8"	6"	6.1/2"	8	1.1/4"	7"	7.1/2"	8	1.1/2"	9.1/4"	9.3/4"
5"	8	3/4"	3.1/4"	3.3/4"	8	3/4"	4"	4.1/2"	8	7/8"	5"	5.1/2"	8	1"	5.3/4"	6.1/4"	8	1.1/4"	6.3/4"	7.1/4"	8	1.1/2"	9"	9.1/2"	8	1.3/4"	11"	11.1/2"
6"	8	3/4"	3.1/4"	3.3/4"	12	3/4"	4.1/4"	4.3/4"	12	7/8"	5.1/4"	5.3/4"	12	1"	6"	61/2"	12	1.1/8"	7"	7.1/2"	12	1.3/8"	9.1/2"	10"	8	2"	13"	13.1/2"
8"	8	3/4"	3.1/2"	4"	12	7/8"	4.3/4"	5.1/4"	12	1"	6"	6.1/2"	12	1.1/8"	7"	7.1/2"	12	1.3/8"	8"	8.1/2"	12	1.5/8"	10.3/4"	11.1/4"	12	2"	14.1/2"	1 5 "
10"	12	7/8"	3.3/4"	4.1/2"	16	1"	5.1/4"	6"	16	1.1/8"	6.3/4"	7.1/4"	16	1.1/4"	7.3/4"	8.1/4"	16	1.3/8"	8.1/2"	9"	12	1.7/8"	12.3/4"	13.1/4"	12	2.1/2"	18.1/2"	19"
12"	12	7/8"	4"	4.1/2"	16	1.1/8"	5.3/4"	6.1/2"	16	1.1/4"	7.1/4"	7.3/4"	20	1.1/4"	8"	8.1/2"	20	1.3/8	9.1/4"	9.3/4"	16	2"	14.1/4"	14.3/4"	12	2.3/4"	20.1/2"	21"
14"	12	1"	4.1/4"	5"	20	1.1/8"	6"	6.3/4"	20	1.1/4"	7.1/2"	8"	20	1.3/8"	8.1/2"	9"	20	1.1/2"	10"	10.1/2"	16	2.1/4"	15.1/2"	16"				
16"	16	1"	4.1/2"	5.1/4"	20	1.1/4"	6.1/2"	7.1/4"	20	1.3/8"	8"	8.1/2"	20	1.1/2"	9.1/4"	9.3/4"	20	1.5/8"	10.1/2"	11"	16	2.1/2"	17"	17.1/2"				
18"	16	1.1/8"	4.3/4"	5.3/4"	24	1.1/4"	6.3/4"	7.1/2 "	24	1.3/8"	8.1/4"	8.3/4"	20	1.5/8"	10"	10.1/2"	20	1.7/8"	12.1/4"	12.3/4"	16	2.3/4"	18.3/4"	19.1/4"				
20"	20	1.1/8"	5.1/4"	6"	24	1.1/4"	7	8"	24	1.1/2"	9"	9.1/2"	24	1.5/8"	10.3/4"	11.1/4"	20	2"	13"	13.1/2"	16	3"	20.1/2"	21"				
24"	20	1.1/4"	5.3/4"	6.3/4"	24	1.1/2"	7.3/4"	9"	24	1.3/4"	10"	10.1/2"	24	1.7/8"	12.1/4"	12.3/4"	20	2.1/2"	16.1/2"	17"	16	3.1/2"	23.1/2"	24"				